

Date: \_\_\_\_\_ Job Name: \_\_\_\_\_ Mark: \_\_\_\_\_

Reference: \_\_\_\_\_ Unit Location: \_\_\_\_\_ Prepared By: \_\_\_\_\_

Engineer: \_\_\_\_\_ Contractor: \_\_\_\_\_ Approval: \_\_\_\_\_

Expected Job Date: \_\_\_\_\_ Notes: \_\_\_\_\_

**UNIT OPTIONS:**

- |   |  |
|---|--|
| <input type="checkbox"/> ADA Fan/Light Control                    | <input type="checkbox"/> Manual Pull Station           |
| <input type="checkbox"/> ClockBox                                 | <input type="checkbox"/> Top Cover                     |
| <input type="checkbox"/> Custom Color <b>Specify Color:</b> _____ | <input type="checkbox"/> Make-Up Air Control Module    |
| <input type="checkbox"/> Test Tank                                | <input type="checkbox"/> Limiting Speed Control Module |

**DISCONNECT OPTIONS:**

- 3/4" NPT Natural Gas
- Electric **\*Specify NEMA: 220VAC** =  14-50R  6-20R **120VAC** =  5-15R  5-20R
- Dual Element (includes 3/4" NPT Natural Gas and Electric)  
**\*Specify NEMA: 220VAC** =  14-50R  6-20R **120VAC** =  5-15R  5-20R
- Dual Receptacle **\*Specify NEMA: 220VAC** =  6-20R **120VAC** =  5-15R  5-20R

**GENERAL FEATURES:**

- Wall Mounted
- Pre-Engineered Fire Suppression System
- Variable Fan Speed Control
- Two Step Pre-Suppression
- Plenum Nozzle
- MAIN Power Switch
- Reset Switch
- Light Switch
- Pressure Gauge
- Temperature Switches
- Hard Wired Fuel Source Disconnect
- Dry Alarm Contacts
- On Board Diagnostics
- Status LED
- Trouble Signal
- Service Key
- Audible Buzzer (90dB)
- Service Switch
- Pressure Switch
- Grease Baffle w/ Drip Tray
- ETL/CSA Listed

FEATURES	DESCRIPTION
<b>Compliance</b>	UL300A    NSF    UL507
<b>Canopy Width</b>	36 Inches
<b>Dimensions In.</b>	35-7/8 x 19-3/8 x 10-1/2
<b>Weight Lbs.</b>	56.8
<b>Voltage / Hz / Amps</b>	120 / 60 / 6.3
<b>MOCP</b>	15A
<b>Fire Control</b>	Programmable Logic Controller
<b>Tank Type / Pressure / Volume</b>	Stainless Steel / 102+-8% Psi / 1.84 Liters
<b>Venting / Fan Type / Speed</b>	Ducted / Roof Mount / Variable Speed
<b>CFM</b>	357 ~ 499
<b>Min / Max Installation Height</b>	30 / 36 Inches
<b>Duct Collar (In. / mm)</b>	7 / 177.8
<b>Sound Rating</b>	61 / 73 dB
<b>Finish</b>	18 & 20 GA 304 Brushed Stainless Steel
<b>Lighting</b>	(1) Shatter-Proof 60-Watt Bulb
<b>Suppression Agent</b>	Low pH Wet Chemical Amerex 660
<b>No. of Nozzles / Spray</b>	4 / 60 Degree Conical
<b>Actuation Type</b>	Mechanical Fail-Safe
<b>Protection Device / Limit</b>	3 Globe Links / 280°F