

Date: \_\_\_\_\_ Job Name: \_\_\_\_\_ Mark: \_\_\_\_\_

Reference: \_\_\_\_\_ Unit Location: \_\_\_\_\_ Prepared By: \_\_\_\_\_

Engineer: \_\_\_\_\_ Contractor: \_\_\_\_\_ Approval: \_\_\_\_\_

Expected Job Date: \_\_\_\_\_ Notes: \_\_\_\_\_

**UNIT OPTIONS:**

- |   |  |
|---|--|
| <input type="checkbox"/> ADA Fan/Light Control                    | <input type="checkbox"/> Manual Pull Station |
| <input type="checkbox"/> ClockBox                                 | <input type="checkbox"/> Top Cover           |
| <input type="checkbox"/> Custom Color <b>Specify Color:</b> _____ | <input type="checkbox"/> Test Tank           |

**DISCONNECT OPTIONS:**

- 3/4" NPT Natural Gas
- Electric **\*Specify NEMA: 220VAC =**  14-50R  6-20R **120VAC =**  5-15R  5-20R
- Dual Element (includes 3/4" NPT Natural Gas and Electric)  
**\*Specify NEMA: 220VAC =**  14-50R  6-20R **120VAC =**  5-15R  5-20R
- Dual Receptacle **\*Specify NEMA: 220VAC =**  6-20R **120VAC =**  5-15R  5-20R

**GENERAL FEATURES:**

- Cabinet or Wall Mounted
- Pre-Engineered, Pre-Installed Fire Suppression System
- Two Speed Fan Control (HI/LOW)
- Reset Switch
- Light Switch
- Pressure Gauge
- Hard Wired Fuel Source Disconnect
- Dry Alarm Contacts
- Safety Pin Lockout
- Audible Buzzer (90dB)
- Charcoal Air Filter
- ETL/CSA Listed
- Spot welded steel construction, with hemmed edges
- Activation by fast response mechanical links, 250°F
- Extinguishing agent is a wet chemical potassium citrate or Potassium acetate solution in a pressurized cylinder

FEATURES	DESCRIPTION
<b>Compliance</b>	UL300A      UL507
<b>Canopy Width</b>	30 Inches
<b>Dimensions In.</b>	30 x 19.25 x 7
<b>Weight Lbs.</b>	33.25
<b>Voltage / Hz / Amps</b>	120 / 60 / 1.2
<b>MOCP</b>	15A
<b>Fire Control</b>	Mechanical Actuation
<b>Tank Type / Pressure / Volume</b>	Steel / 102+-8% Psi / 900 Milliliters
<b>Venting / Fan Type / Speed</b>	Recirculating / Front Discharge / 2 Speed
<b>CFM</b>	30 ~ 44 +-2.5%
<b>Min / Max Installation Height</b>	18 / 26 Inches
<b>Duct Collar (In. / mm)</b>	N/A
<b>Sound Rating</b>	57 / 66 dB
<b>Finish</b>	Painted White Powder Coat, Optional Stainless-Steel Finish
<b>Lighting</b>	(2) Reflective 45-Watt Bulbs
<b>Suppression Agent</b>	Low pH Wet Chemical Amerex 660
<b>No. of Nozzles / Spray</b>	2 / 60 Degree Conical
<b>Actuation Type</b>	Mechanical Fail-Safe
<b>Protection Device / Limit</b>	2 Globe Links / 250°F