

D1000-E DATASHEET

D1000-E ASY-200074																	
MATERIAL INFORMATION																	
TYPE	QTY	BRAND	MODEL	Construction Data Report	COLORS AVAILABLE	MOUNTING CONFIG.	MATERIAL SPECIFICATIONS					COMPONENT INFORMATION					
							LENGTH (In.)	DEPTH (In.)	HEIGHT (In.)	WEIGHT (Lbs.)	MATERIAL	MOUNTING HEIGHT	VOLTAGE	PHASE	BREAKER SIZE	CONTINOUS OPERATING	D1000-E
Option	1	DENLAR	D1000-ED	3133316CRT-003	N/A	Surface Mount or Flush Mount	8	3.7	8	6.8	Galvanized	See Local Codes	110 VAC COIL	1	NA	0.25	Specify NEMA 14-50R, 6-20R, 6-15R, or 5-15R

D1000-E ASY-200074

NOTES:
1 Enclosure can be Flush or Surface mounted.
2 A 220 VAC 50Amp Contactor is provided in the Assembly (Not Shown)
3 Installer will provide circuitry proper for the associated range up to 220 VAC and 50 Amps
4 A NEMA 14-50R, 6-20R, 5-20R, OR 5-15R is provided in the Assembly
5 A 120 VAC Plug connection coming from the Hood or Clock Box is needed to be plugged in (Refer to Devices Flow Chart LAB-110084)

DENLAR

FIRE PROTECTION

PRE-ENGINEERED RANGE HOODS

The World's Only Fail-Safe UL300A Hood