



	<b>D1000</b>	<b>Designer</b>	<b>Guardian III</b>
Fully Integrated Hood System	YES	YES	NO
18 Gauge Stainless Steel/Commercial Construction-with Many NFPA 96 Features	YES	YES	NO
Fail Safe Mechanical Suppressant Release, Requiring No 110 Volt Power or Battery	YES	YES	NO
Commercial Style Stainless Steel Grease Filter and Collection	YES	NO	NO
Globe Fusible Link and Fire Suppression Nozzle in the Fan Compartment	YES	NO	NO
Sealed Unit-National Sanitary Foundation (NSF) Approved	YES	NO	NO
Factory Aligned Nozzles	YES	YES	NO (2 Nozzles, adjusted in the field)
2 Temperature Switches to Automatically Turn on Fan	YES	NO	NO
Temperature Sensing to Automatically Turn Off Range Power Source	YES	NO	NO
Relay Control Output to Both Remote and Local Alarm	YES	YES	NO
Electric, Gas, or Dual Element Disconnect	YES	YES	NO
120V Power Supply	YES	YES	OPTIONAL
Tested to UL300A	YES	YES	YES
Tested to UL507 (fan)	YES	YES	NO FAN
Quick/Easy Service/Removal	YES	YES	NO
Fast Simple Install-No retrofit or Modifications	YES	YES	NO
Complies with the NFPA101 Life Safety Code	YES*	NO	NO
Warranty	TWO YEARS	TWO YEARS	ONE YEAR

\*The D1000 offers an upgrade that provides an upgraded fan that is at least 500CFM, a Manual Pull Station, and our CLOCKBOX (password protected element timer and lockout system)

